

Worksheet: OOP and Recursion

1

1. the parent class of Dog is Pet. Does Pet have a parent type? If so, what is it?
2. how many arguments does line C pass?
3. how many arguments does line B pass?
4. on another paper, draw what the frames and object(s) will look like after line A. (check with PythonTutor)

```
class Pet:
    def __init__(self, name):
        self.name = name # A

class Dog(Pet):
    def __init__(self, name, age):
        self.age = age
        Pet.__init__(self, name) # B

pup = Dog("Sam", 1) # C
```

2

```
def fact(n):
    if n == 0:
        return 1
    return n * fact(n-1)

# what is fact(5)
```

```
def fib(n):
    if n < 2:
        return n
    return fib(n-1) + fib(n-2)

# what is fib(6)?
```

3

```
def f(n):
    print(n)
    if n < 9:
        f(n + 1)

# what does f(7) print?
```

```
def g(n):
    if n < 9:
        g(n + 1)
    print(n)

# what does g(7) print?
```

4

```
def M(n):
    print(n)
    if n > 1:
        M(n-1)
        print(n)

# what does M(3) print?
```

```
B = []
def h(A):
    if len(A) > 0:
        h(A[1:])
        B.append(A[0])
h([2, 5, 6, 3])
# what is in B?
```


5

```
class Node:
    def __init__(self, val):
        self.val = val
        self.next = None

    def tot(self):
        if self.next != None:
            return self.val + self.next.tot()
        return self.val

    def __getitem__(self, idx):
        if idx == 0:
            return self.val
        return self.next[idx-1]

A = Node(3)
B = Node(5)
C = Node(7)
A.next = B
B.next = C
```



1. finish the PythonTutor picture on the right
2. what is `C.tot()`? `B.tot()`? `A.tot()`?
3. what is `A[0]`? `A[2]`?
4. what kind of error does `A[-1]` produce?
5. how would the PythonTutor change if we added `C.next = A`?
6. what would `C[3]` be, given above change?
7. what would `A.tot()` do, give above change?