
# [544] File Formats

Tyler Caraza-Harter

### Learning Objectives

- describe different file formats in terms of orientation, encoding, compression, and schemas
- write code to use parquet files
- differentiate between transactions workloads and analytics workloads
- explain the motivation for using an ETL (extract transform load) process to copy data from an transactions processing system to an analytics processing system

File systems let us give names to sequences of bytes (files) and hierarchically organize those files (via directories). We usually want some structure for those bytes.



#### File Formats

	CSV	Parquet
orientation	row	column
encoding	text	binary
compression	none	snappy
schemas	inferred	explicit

Demos

## File Layout

#### Goals

- efficient input/output from storage (large enough reads/writes, sequential accesses)
- minimize parsing/deserialization computation time

#### Assumptions

- many file systems will try to map consecutive bytes of a file to consecutive blocks on a storage device (but note that in some cases sequential file I/O becomes random disk I/O)
- need to clarify assumptions about how code will access the data (for example, one whole column? a row at a time?)

	1						
ACW00011604	17.1167	-61.7833	10.1	ST JOHNS COOLIDGE FLD			
ACW00011647	17.1333	-61.7833	19.2	ST JOHNS			
AE000041196	25.3330	55.5170	34.0	SHARJAH INTER. AIRP	GS	N 41196	
AEM00041194	25.2550	55.3640	10.4	DUBAI INTL		41194	
AEM00041217	24.4330	54.6510	26.8	ABU DHABI INTL		41217	
AEM00041218	24.2620	55.6090	264.9	AL AIN INTL		41 <mark>21</mark> 8	
AF000040930	35.3170	69.0170	3366.0	NORTH-SALANG	GS	N 40930	
AFM00040938	34.2100	62.2280	977.2	HERAT		40938	ghcnd-stations.txt
AFM00040948	34.5660	69.2120	1791.3	KABUL INTL		40948	
AFM00040990	31.5000	65.8500	1010.0	KANDAHAR AIRPORT		40990	
AG000060390	36.7167	3.2500	24.0	ALGER-DAR EL BEIDA	GS	N 60390	
AG000060590	30.5667	2.8667	397.0	EL-GOLEA	GS	N 60590	
AG000060611	28.0500	9.6331	561.0	IN-AMENAS	GS	N 60611	
AG000060680	22.8000	5.4331	1362.0	TAMANRASSET	GS	N 60680	good: just read the one
AGE00135039	35.7297	0.6500	50.0	ORAN-HOPITAL MILITAIRE			
AGE00147704	36.9700	7.7900	161.0	ANNABA-CAP DE GARDE			block containing the ro
AGE00147705	36.7800	3.0700	59.0	ALGIERS-VILLE/UNIVERSITE			<u> </u>
AGE00147706	36.8000	3.0300	344.0	ALGIERS-BOUZAREAH			

bad: need to read everything to access any one column

## File Layout

#### Goals

- efficient input/output from storage (large enough reads/writes, sequential accesses)
- minimize parsing/deserialization computation time

#### Assumptions

- many file systems will try to map consecutive bytes of a file to consecutive blocks on a storage device (but note that in some cases sequential file I/O becomes random disk I/O)
- need to clarify assumptions about how code will access the data (for example, one whole column? a row at a time?)

#### Major access patterns

- transactions processing: reading/changing a row (or few rows) as needed by an application (note: "transaction" has other meanings for databases as well -- more later...)
- analytics processing: computing over many rows for specific columns

coll	col2	col3
l	5	Α
2	6	В
3	7	С
4	8	D

row-oriented file: I 5 A 2 6 B 3 7 C 4 8 D

col-oriented file:

12345678ABCD

position in file


coll	col2	col3
I	5	Α
2	6	В
3	7	С
4	8	D

row-oriented file:



transactional access pattern

col-oriented file:



coll	col2	col3
I	5	Α
2	6	В
3	7	С
4	8	D




analytics access pattern

col-oriented file:



coll	col2	col3
I	5	Α
2	6	В
3	7	С
4	8	D




#### File Formats


	CSV	Parquet
orientation	row	column
encoding	text	binary
compression	none	snappy
schemas	inferred	explicit

Demos


# Text vs. Binary




# Text vs. Binary



### Text vs. Binary





#### File Formats

	CSV	Parquet
orientation	row column	
encoding	text	binary
compression	none	snappy
schemas	inferred	explicit


Demos

### Compression

Idea: avoid repeating yourself

- repetitive datasets are more compressible
- more compute time finding repetition => better compression ratio (original/compressed size)

Example: snappy compression (parquet default):




"[Snappy] does not aim for maximum compression, or compatibility with any other compression library; instead, it aims for very high speeds and reasonable compression."

#### Snappy documentation

- https://github.com/google/snappy
- https://github.com/google/snappy/blob/main/format\_description.txt


## Challenge: Small Updates



can't just update this first address in isolation (need to rewrite other parts of the file)

### Compression Window/Block

"the current Snappy compressor works in 32 kB blocks and does not do matching across blocks"



will compression generally work better for row-oriented formats or column-oriented formats?

#### File Formats

	CSV	Parquet	
orientation	row	column	
encoding	text	binary	
compression	none	snappy	
schemas	inferred	explicit	

Demos

### Schemas

Schema: "A description of the structure of some data, including its fields and datatypes." -- Kleppmann

#### CSVs:

- in the file, everything is text
- pd.read\_csv("file.csv", dtype={"coll": str, "col2": int, ...}) # specify schema (annoying)

schema specified as a dict

• pd.read\_csv("file.csv", dtype=None) # infer schema (slow, error prone!)

#### parquet files:

- type specification is part of the file
- fast: no need for very slow schema inference



File Formats

Demos...

File Formats

Demos...

- tables and queries
- architecture
- transactions vs. analytics

### **Tables**

#### tbl\_purpose

id	loan_purpose
1	Home purchase
2	Home improvement
3	Refinancing

#### tbl\_action

id	action_taken
1	Loan originated
2	Application approved but not accepted
3	Application denied by financial institution
4	Application withdrawn by applicant
5	File closed for incompleteness
6	Loan purchased by the institution
7	Preapproval request denied by financial
8	Preapproval request approved but not accepted

#### Databases store a collection of tables

- schemas define the columns/types for each table
- IDs/keys let us relate multiple tables (for example, the first loan is in Alaska)

code	abbr	name
1	AL	Alabama
2	AK	Alaska
4	ΑZ	Arizona
5	AR	Arkansas
6	CA	California
8	CO	Colorado
9	CT	Connecticut
10	DE	Delaware
•••	•••	 string

#### tbl\_loan

id	purpose	action	state	amount	rate
1	2	1	2	20000	5.0
2	1	1	8	300000	3.0
3	1	4	10	450000	3.2
•••	• • •	•••	•••	•••	•••

int float

### Queries

#### tbl\_purpose

id	loan_purpose
1	Home purchase
2	Home improvement
3	Refinancing

code	abbr	name
1	AL	Alabama
2	AK	Alaska
4	ΑZ	Arizona
5	AR	Arkansas
6	CA	California
8	CO	Colorado
9	CT	Connecticut
10	DE	Delaware
•••	•••	•••

id	action_taken
1	Loan originated
2	Application approved but not accepted
3	Application denied by financial institution
4	Application withdrawn by applicant
5	File closed for incompleteness
6	Loan purchased by the institution
7	Preapproval request denied by financial
8	Preapproval request approved but not accepted

tbl\_action

#### tbl\_loan

id	purpose	action	state	amount	rate
1	2	1	2	20000	5.0
2	1	1	8	300000	3.0
3	1	4	10	450000	3.2
•••		•••	•••	• • •	•••
	1 1 1	; ; ; ;	 		

#### Queries let us

- ask questions about the data (like, what is the name of the state with "WI" as an abbreviation)
- make changes to the data (like insert Puerto Rico as a row in tbl\_state)

# SQL

#### tbl\_purpose

id	loan_purpose
1	Home purchase
2	Home improvement
3	Refinancing

code	abbr	name
1	AL	Alabama
2	AK	Alaska
4	ΑZ	Arizona
5	AR	Arkansas
6	CA	California
8	CO	Colorado
9	CT	Connecticut
10	DE	Delaware
•••	•••	•••

### tbl\_action

id	action_taken
1	Loan originated
2	Application approved but not accepted
3	Application denied by financial institution
4	Application withdrawn by applicant
5	File closed for incompleteness
6	Loan purchased by the institution
7	Preapproval request denied by financial
8	Preapproval request approved but not accepted

#### tbl\_loan

id	purpose	action	state	amount	rate
1	2	1	2	20000	5.0
2	1	1	8	300000	3.0
3	1	4	10	450000	3.2
•••	• • •	•••	•••	• • •	•••

#### Structure Query Language (SQL)

- most popular/famous query language
- ask questions about the data: SELECT
- make changes to the data: INSERT, UPDATE, DELETE

# SQL

#### tbl\_purpose

id	loan_purpose
1	Home purchase
2	Home improvement
3	Refinancing

code	abbr	name
1	AL	Alabama
2	AK	Alaska
4	ΑZ	Arizona
5	AR	Arkansas
6	CA	California
8	CO	Colorado
9	CT	Connecticut
10	DE	Delaware
•••	•••	•••

#### tbl\_action

id	action_taken
1	Loan originated
2	Application approved but not accepted
3	Application denied by financial institution
4	Application withdrawn by applicant
5	File closed for incompleteness
6	Loan purchased by the institution
7	Preapproval request denied by financial
8	Preapproval request approved but not accepted

#### tbl\_loan

id	purpose	action	state	amount	rate
1	2	1	2	20000	5.0
2	1	1	8	300000	3.0
3	1	4	10	450000	3.2
•••	 	•••	•••		•••

#### Structure Query Language (SQL)

- most popular/famous query language
- ask questions about the data: SELECT
- make changes to the data: INSERT, UPDATE, DELETE

#### SELECT AVG(rate) FROM tbl\_loan;

SELECT amount, rate FROM tbl\_loan WHERE id = 544; INSERT INTO tbl\_loan (...) VALUES (...);

analytics (calculate over many/all rows, few colums)

transactions (working with whole row or few rows at a time)

File Formats

Demos

- tables and queries
- architecture
- transactions vs. analytics

Architecture: big picture of a system's components/subsystems


Databases manage all the resources we've learned about:

- storage
- memory
- network
- compute

storage structures in files

#### example database architecture:

(Chapter 1 of Database Internals, by Petrov)



Architecture: big picture of a system's components/subsystems

Databases manage all the resources we've learned about:

- storage
- memory
- network
- compute

Cluster Client Communication Communication Query Processor Query Parser Query Optimizer Execution Engine Remote Local Execution Execution Storage Engine O'REILLY" **Database** Transaction Lock Manager Manager Internals Access Methods Recovery Buffer Manager Manager

Figure 1-1. Architecture of a database management system

(Chapter 1 of Database Internals, by Petrov)

Alex Petrov

example database architecture:

Transport

storage structures in files

in-memory cache

Architecture: big picture of a system's components/subsystems

Databases manage all the resources we've learned about:

- storage
- memory
- network
- compute

Query Optimizer

Execution Engine

Remote
Execution

Execution

Storage Engine

Transaction
Manager

Access Methods

storage structures in files

in-memory cache

example database architecture:

Query Parser

Client

Communication

SQL queries/results

sent over network

O'REILLY"

**Database** 

Alex Petrov

Internals

Transport

Cluster

Communication

Query Processor

Buffer Manager

Figure 1-1. Architecture of a database management system (Chapter 1 of Database Internals, by Petrov)

Recovery

Manager

storage structures


in files

Architecture: big picture of a system's components/subsystems

Databases manage all the resources we've learned about:


- storage
- memory
- network
- compute

example database architecture:




(Chapter 1 of Database Internals, by Petrov)

### Files vs. Databases (storage+compute coupling)



Databases pros/cons (relative to just using files):

- "[databases] tightly couple their internal layout of the data and indexes in ondisk files with their highly optimized query processing engines, thus providing very fast computations on the stored data..."
- "Databases store data in complex (often proprietary) formats that are typically highly optimized for only that database's SQL processing engine to read. This means other processing tools, like machine learning and deep learning systems, cannot efficiently access the data (except by inefficiently reading all the data from the database)."



File Formats

Demos

- tables and queries
- architecture
- transactions vs. analytics

### Transactions vs. Analytics

SELECT AVG(rate) FROM tbl\_loan;

SELECT amount, rate FROM tbl\_loan WHERE id = 544; INSERT INTO tbl\_loan (...) VALUES (...);

analytics (calculate over many/all rows, few colums)

transactions (working with whole row or few rows at a time)

SQL (as a language) works great for both transactions and analytics

Problem: it's hard for a single database (SQL or otherwise) to be good at both

Main database types:


- OLTP (online transactions processing)
- OLAP (online analytics processing)

"The meaning of online in OLAP is unclear; it probably refers to the fact that queries are not just for predefined reports, but that analysts use the OLAP system interactively for explorative queries." ~ Kleppmann.


### Transactions vs. Analytics

Typical storage design

#### example database architecture:



# What if you need transactions AND analytics?






Figure 3-8. Simplified outline of ETL into a data warehouse. (Chapter 3 of Data-Intensive Applications, by Kleppmann)

#### Vocab

- Data warehouse: the OLAP database where we combine data from many sources
- ETL: extract-transform-load (process for getting data out of OLTP DBs and into OLAP DB)