


# [320] Search Order and Queue Structures

Yiyin Shen

# Tracing DFS

```
def find(self, dst):  
    self.graph.visited.add(self)  
  
    if self == dst:  
        return (self.name,)  
  
    for child in self.children:  
        if not child in self.graph.visited:  
            childpath = child.find(dst)  
            if childpath:  
                return (self.name,) + childpath  
  
    return None
```

A.find(D)




# Queueing Structures

# Shortest Weighted Path

What path will DFS choose?

What path will BFS choose?

What path would you choose?




# Work queues ("to do" list)


**Stack**  
(FILO)



**Queue**  
(FIFO)



**Priority Queue**



# Work queues ("to do" list)

**Stack**  
(FILO)



```
L.append(x)
```

```
x = L.pop(-1)
```

**Queue**  
(FIFO)

front ←



```
x = L.pop(0)
```

```
L.append(x)
```

**Priority Queue**

smallest/biggest ←



```
L.sort()  
x = L.pop(-1)
```

```
L.append(x)
```

*what operations are slow?*

# Work queues ("to do" list)

**Stack**  
(FILO)



```
L.append(x)
```

```
x = L.pop(-1)
```

**Queue**  
(FIFO)

front ←



! 

```
x = L.pop(0)
```

```
L.append(x)
```

**Priority Queue**

smallest/biggest ←



! 

```
L.sort()  
x = L.pop(-1)
```

```
L.append(x)
```

*what operations are slow?*